

## TXT-2

### Service packer

#### APPLICATIONS

- Remedial work and service applications
- Acidizing
- Fracturing
- Squeeze cementing
- Casing test applications

#### BENEFITS

- Maximum pressure performance
- High running speed and ease of operations reduce rig time

#### FEATURES

- 8,000 psi [55,158 kPa] nominal pressure rating
- Large internal bypass area to maximize running and circulating rates
- Multiple hold-down button slip assembly for maximum pressure performance
- Three-piece packing element system for reliable, proven performance
- Multiple jay configurations available
- Convertible jay configuration with kit


The TXT-2 service packer is a compression-set retrievable service packer used for remedial applications such as squeeze cementing, fracturing, acidizing, and other operations where high pressure differentials are required.

#### Main features

- Mechanically set
- Retrievable
- For use as a service packer

#### Setting and operation

The collet releases during setting by applying tubing weight, which closes the bypass. Carbide-inserted drag blocks, carbide-inserted slips, and a three-piece packing element system enhance packer performance. Hydraulic hold-down buttons are protected during running or circulating, minimizing damage potential.



#### TXT-2 Service Packer Specifications

Casing OD, in [mm]	Casing Weight Range, lbm/ft [kg/m]	Casing ID Range, Min., in [mm]	Casing ID Range, Max., in [mm]	Tool OD, Max., in [mm]	Thread
4.5 [114.30]	9.5–13.5 [14.14–20.09]	3.920 [99.57]	4.090 [103.88]	3.760 [95.50]	2.375 EU 8 RD
5 [127.00]	15–18 [22.32–26.79]	4.276 [108.61]	4.408 [111.96]	4.110 [104.39]	2.375 EU 8 RD
5.5 [139.70]	20–23 [29.76–34.22]	4.670 [118.62]	4.778 [121.36]	4.500 [114.30]	2.375 EU 8 RD
5.5 [139.70]	15.5–20 [23.07–29.76]	4.778 [121.36]	4.950 [125.73]	4.640 [117.86]	2.375 EU 8 RD
5.5 [139.70]	13–15.5 [19.35–23.07]	4.950 [125.73]	5.044 [128.12]	4.760 [120.90]	2.375 EU 8 RD
5.75 [146.05]	18–21.9 [26.79–32.95]	5.039 [127.97]	5.354 [135.99]	4.817 [122.35]	2.375 EUE 8 RD
6.00 [152.40]	20–23 [29.76–34.22]	5.191 [131.85]	5.390 [136.91]	5.062 [128.57]	2.375 EUE 8 RD
6.625 [168.27]	24–28 [35.72–41.67]	5.791 [147.09]	5.920 [150.37]	5.588 [141.94]	2.875 EUE 8 RD
7 [177.80]	32–35 [47.62–52.09]	6.004 [152.50]	6.094 [154.78]	5.812 [147.62]	2.875 EU 8 RD
7 [177.80]	26–29 [38.69–43.16]	6.184 [157.07]	6.276 [159.41]	5.950 [151.13]	2.875 EU 8 RD
7 [177.80]	20–26 [29.76–38.69]	6.276 [159.41]	6.456 [163.98]	6.078 [154.38]	2.875 EU 8 RD
7.625 [193.67]	33.7–39 [50.14–58.04]	6.625 [168.27]	6.765 [171.83]	6.453 [163.91]	2.875 EU 8 RD
7.625 [193.67]	26.4–33.7 [39.29–50.15]	6.765 [171.83]	6.969 [177.01]	6.593 [167.46]	2.875 EU 8 RD
7.625 [193.67]	24–29.7 [35.72–44.20]	6.875 [174.62]	7.025 [178.43]	6.672 [169.46]	2.875 EU 8 RD
7.625 [193.67]	20–24 [29.76–41.67]	7.025 [178.43]	7.125 [180.97]	6.812 [173.02]	2.875 EU 8 RD

TXT-2 service packer.